

**INSTALLATION STEPS:**

- 1.) POSITION DOOR ABOVE FLOOR PIVOT, PUSHING SLOT IN FLOOR CLOSER ARM INTO PIVOT
- 2.) PUSH DOOR INTO OPENING, ALIGNING SLOT IN PIVOT ARM AT TOP RAIL WITH PIVOT OF OVER HEAD CLOSER
- 3.) LOCK PIVOT INTO PLACE BY PLACING LOCKING PLATE AGAINST PIVOT ARM AND TIGHTENING SCREWS
- 4.) TURN DOOR WITHIN JAMB TO ACCESS ADJUSTMENT SCREW
- 5.) TURN ADJUSTMENT SCREW TO ALIGN DOOR WITHIN JAMB
- 6.) ONCE ALIGNED, LOCK PIVOT ARM INTO TOP RAIL WITH (2) SCREWS ABOVE TOP RAIL
- 7.) COVER CUTOUT FOR CLOSER ARM WITH COVER PLATE



1 ISOMETRIC OF DOOR PREPPED FOR USE WITH OVERHEAD CLOSER  
NTS

NOTE: THIS PRINT IS FURNISHED BY AMERICAN ARCHITECTURAL Inc. WITH THE UNDERSTANDING THAT IT WILL BE USED TO FABRICATE AND COORDINATE THE INSTALLATION OF WORK CONTRACTED TO AMERICAN ARCHITECTURAL Inc. ONLY. AMERICAN ARCHITECTURAL Inc. IS NOT RESPONSIBLE FOR ACTIONS MADE BY ANYONE OTHER THAN AMERICAN ARCHITECTURAL Inc. BASED ON THE INFORMATION IN THIS PRINT.

<b>D-2</b>	DATE:	MAY 07
	DRAWN BY:	NRS
	CHECKED BY:	
	SCALE:	AS NOTED
PROJECT NUMBER:		
06-378		

PROJECT:	AMERICAN DOOR
LOCATION:	2260 STATE ROAD, BENSALEM, PA
ARCHITECT:	N/A
CONTRACTOR:	N/A
DRAWING TITLE:	AMERICAN DOOR OVERHEAD CLOSER SYSTEM

REVISIONS					
No.	Date	Revision/Issue	No.	Date	Revision/Issue

RECORD OF PRINTS							
DATE	QUANT.	TO	FOR	DATE	QUANT.	TO	FOR